CONSTRUCTION AND ANALYSIS OF FLAT PLATE SOLAR WATER HEATER SYSTEM

A Thesis
By

Md Abu Noman (ID: ME2103025349)
Md. Nur Nabi (ID: ME2003022169)
Md Mohoshin Hossen (ID: ME2003022051)
KH. Momin Hossain (ID: ME2103025272)
Md. Sabbir Hosen Leon (ID: ME2103025475)

Under the Supervision of
Ibrahim Khalil Apurba
Lecturer

DEPARTMENT OF MECHANICAL ENGINEERING
SONARGAON UNIVERSITY (SU), DHAKA

MAY 19, 2025

Construction and Analysis of Flat plate Solar Water Heater System

A thesis report submitted to the department of mechanical engineering for the partial fulfillment of the degree of Bachelor of Science in Mechanical Engineering.

A Thesis By

Md Abu Noman
ID No: ME2103025349

KH. Momin Hossain
ID No: ME2103025272

Md. Nur Nabi
ID No: ME2003022169

Md. Sabbir Hosen Leon
ID No: ME2103025475

Md Mohoshin Hossen
ID No: ME2003022051

.....

Supervisor
Ibrahim Khalil Apurba
Lecturer of Mechanical Engineering



DEPARTMENT OF MECHANICAL ENGINEERING
SONARGAON UNIVERSITY (SU), DHAKA

Dhaka, Bangladesh
May 19, 2025

Declaration

It is declared hereby that this thesis paper or any part of it has not been submitted to anywhere else for the award any degree.

…….
Md Abu Noman

……
Md. Nur Nabi

…….
Md. Mohoshin Hossen

…….
KH. Momin Hossain

……
Md.Sabbir Hosen Leon

Certification

This is to certify that this project entitled "**Construction & Analysis of Flat plate Solar Water Heater System**" is done by the following students under my direct supervision. This project work has been carried out by them in the laboratories of the Department of Mechanical Engineering under the Faculty of Engineering, Sonargaon University (SU) in partial fulfillment of the requirements for the degree of Bachelor of Science in Mechanical Engineering.

Supervisor:

……

Ibrahim Khalil Apurba

Lecturer, Sonargaon University (SU) Dhaka-1215,

Bangladesh.

Acknowledgement

At first, we would like to express our gratitude to Almighty Allah for giving us the strength and opportunity to complete our dissertation within the scheduled time successfully. The presentation of the project paper represents the collaborative efforts and generous support of a number of individuals. The Department of Mechanical Engineering (ME), Sonargaon University provided important subject expertise and information technology services to carry out the project work successfully. We feel proud to express our deep sense of gratitude to our reverend teacher, guide and supervisor, for his day to day supervision, dexterous management, adept analysis, keen interest, optimistic counseling, and unremitting backup. We are very much indebted to Ibrahim Khalil Apurba, Lecturer, Department of Mechanical Engineering, Sonargaon University, for including a dissertation as a course in B.Sc. in engineering to strengthen eligibility of students. We would also like to thank those persons of Department of Mechanical, Sonargaon University, for their encouragement and help in our project work.

Abstract

This project introduces a solar water heating system defined as a sustainable solution that leverages solar energy for efficient water heating, minimizing dependence on conventional power sources. The system operates by capturing solar energy through a photovoltaic panel, which is then stored in a battery to ensure continuous energy supply regardless of sunlight variability. An inverter circuit converts the stored DC energy into the appropriate AC voltage and current needed to operate the system. This electrical energy is directed to a burner coil submerged in a water tank, where the coil functions as the main heating element. The heating process can be analyzed in terms of energy transfer, where electrical energy $E = V \times I \times T$ (with V as voltage, I as current, and T as time) is converted into thermal energy $Q = mc\Delta T$ (where m is the water mass, c is the specific heat capacity, and ΔT is the temperature change). This integration enables efficient thermal conversion and storage, offering advantages such as reduced carbon emissions, lower energy bills, and enhanced energy independence. The model highlights the practical application of renewable energy in everyday use, making it suitable for residential and small-scale commercial implementation.

Table of Contents

Declaration ii

Certification iii

Acknowledgement iv

Abstract v

Table of Contents vi

List of Tables viii

List of Figures ix

Chapter 1: Introduction 1

1.1 Introduction 1

1.2 Study Background 2

1.3 Statement Problems 3

1.4 Objectives 3

1.5 Significance of the project 4

1.6 Scope of the project 4

Chapter 2: Literature Review 6

2.1 Literature Review 6

2.2 Overview of This Project 7

2.3 Types of Solar Thermal Heater 7

2.3.1. Active solar water heaters 8

2.3.2. Passive Solar Water Heater 10

2.3.3. Flat-Plate Circulation System 11

2.3.4. Evacuated-tube Circulation System 12
2.4. Solar Water Heating Technology 13
2.5. Comparative Studies of Collector Types 16
2.6. Flat Plate Collectors: History and Evolution 19
2.7. Gaps in Existing System 21
Chapter 3: Methodology 23
3.1 System Methodology 23
3.2 Materials 24
3.3 Material Requirements 26
3.3.1. Main Frame 27
3.3.2. Water Tank 28
3.3.3. Heat Exchanger 28
3.3.4. Isolation Valve 29
3.3.5. Tempering Valve 30
3.4 Block Diagram 30
Chapter 4: System Design and Architecture 32
4.1 Design of the system 32
4.2 Use of Tools and Techniques 33
4.3 Measurement Techniques 34
4.4 Data Collection Procedure 35
Chapter 5: Result and Analysis 37
5.1 Thermal Efficiency Equation 37
5.2 Heat Loss in Flat Plate Collectors 38
5.3 Assumptions for daily demand hot water 39
5.4 Assumptions for Calculations 40

Chapter 6: Conclusion and Recommendations 44

6.1 Conclusion 44

6.2 Recommendations 45

Reference ……13.2

List of Tables

Table No	Table Contain	Page No
Table 1	Materials List	26

List of Figures

Figure No	Figure Contain	Page No
Fig. 2.1	Different types of circulation system	8
Fig. 2.2	Active direct-circulation system	9
Fig. 2.3	Passive Direct Circulation System	10
Fig. 2.4	Flat Plate Collector	11
Fig. 2.5	Evacuated-Tube Collector	12
Fig. 2.6	Image of Flat Plate	14
Fig. 2.7	Image of Evacuated Tube	14
Fig. 2.8	Integral Collector Storage System	15
Fig. 2.9	Thermosiphon System	15
Fig. 2.10	Forced Circulation System	16
Fig. 3.1	Image of Solar Panel	24
Fig. 3.2	Image of the Main Frame	27
Fig. 3.3	Image of Water chamber	28
Fig. 3.4	Image of Heat Exchanger	28
Fig. 3.5	Image of Isolation Valve	29
Fig. 3.6	Image of Tempering Valve	30
Fig. 3.7	Block Diagram of the system	31
Fig. 4.1	Architectural design of the system	32

Chapter 1

Introduction

1.1. Introduction

The world is increasing interested in reducing global warming because of the belief that it may be a real threat and we must find ways to reduce carbon emissions to protect the environment. As a result, there is a heightened interest in renewable energy production that can reduce the future demand for coal and natural gas fired power plants. Renewable power production technologies such as wind farms, photovoltaics, geothermal, hydroelectric, and biomass systems are all receiving a lot of attention. Another, less costly alternative, is solar thermal water heating systems. The term “solar power” can be used to denote either solar thermal systems or photovoltaic systems. Photovoltaic systems generate electricity by using the interaction of sunlight with a semi-conducting material, which frees electrons in the material to create an electric current. In contrast, solar thermal systems use the heat generated by sunlight to heat air or water.

The growing demand for sustainable and eco-friendly energy solutions has led to significant advancements in solar technologies. One such application is the solar water heater, which uses renewable solar energy to provide heated water without depending on conventional power sources. This project, "A Comprehensive Model of Solar Water Heater," aims to demonstrate an efficient and practical system that can be used in residential and small-scale industrial settings. The system is designed using a solar panel to capture solar energy, a 12V battery for energy storage, and an inverter circuit to regulate the electrical output. A burner coil submerged in a water tank acts as the heating element, converting the stored electrical energy into heat to warm the water. This integration showcases a clean and sustainable approach to water heating, promoting the use of renewable energy and reducing dependence on fossil fuels. The model not only highlights the principles of energy conversion and storage but also encourages the adoption of green technologies for everyday needs.

1.2. Study Background

With increasing global concerns over energy consumption and environmental degradation, the search for alternative energy sources has become a priority. Solar energy stands out as one of the most abundant, clean, and renewable resources available. Solar water heating systems have emerged as a practical application of solar technology, helping to reduce dependency on non-renewable energy sources and lowering carbon emissions. Traditional water heating methods rely heavily on electricity or fossil fuels, both of which are costly and contribute to environmental pollution. By utilizing solar panels to convert sunlight into electrical energy, storing it in a 12V battery, and using an inverter circuit to regulate the output for heating a burner coil placed inside a water tank, this project aims to create a highly efficient and sustainable system. This study explores the integration of simple, readily available components to create an affordable and reliable solar water heating model. It provides insights into how solar energy can be effectively harnessed, stored, and utilized to meet basic domestic needs while contributing to a greener future.

Energy is fundamental to human development, but conventional energy sources like coal, oil, and natural gas are limited and harmful to the environment. Growing concerns about climate change, rising fuel costs, and resource depletion have intensified the need for sustainable alternatives. Solar energy, due to its abundance, renewability, and zero carbon footprint, has become a leading solution for clean energy systems. Among the various applications of solar energy, solar water heating represents one of the simplest and most effective methods for utilizing solar power at the domestic level. Traditional solar water heaters directly use thermal energy from sunlight. However, to enhance versatility and allow operation even during low sunlight periods, an electrically assisted model becomes beneficial. This project focuses on creating an electrically powered solar water heating system. A solar panel captures solar radiation and converts it into electrical energy, which is stored in a 12V battery. To ensure compatibility with the heating element, an inverter circuit adjusts the voltage and current. The burner coil, submerged in a water tank, uses this electrical energy to heat the water efficiently. This model bridges two important areas of renewable energy: solar photovoltaic technology (energy conversion and storage) and thermal energy

utilization (water heating). It not only provides a functional solution for hot water needs but also encourages the practical implementation of renewable energy systems in everyday life. The study aims to inspire further innovation in clean energy applications, making sustainable living more accessible and affordable.

1.3. Statement of Problems

Access to reliable and affordable hot water is essential for domestic, industrial, and commercial activities. However, conventional water heating systems primarily rely on electricity or fossil fuels, leading to high energy costs, environmental pollution, and increased carbon emissions. In regions with limited electricity access or frequent power outages, obtaining hot water becomes even more challenging. Despite the availability of solar energy, many existing solar water heating systems are expensive, complex, or dependent solely on direct sunlight, making them less effective during cloudy weather or nighttime. There is a critical need for a simple, cost-effective, and energy-efficient solar water heating model that can store solar energy and provide hot water consistently, even in varying environmental conditions. This project addresses the problem by developing a comprehensive model of a solar-powered water heater that combines solar energy collection, battery storage, and electrical heating. By integrating a solar panel, 12V battery, inverter circuit, burner coil, and water tank, the model aims to deliver a practical, eco-friendly solution that reduces dependence on traditional energy sources and promotes sustainable living.

1.4. Objectives

The main objective of this project is to design and develop a comprehensive solar- powered water heating system that is efficient, cost-effective, and environmentally friendly. The specific objectives are:

- To harness solar energy using a solar panel and convert it into electrical energy for storage in a 12V battery for continuous availability, even during non-sunny periods.
- To design an inverter circuit that regulates and supplies the required power to the heating element using a burner coil powered by the stored solar energy.
- To promote eco-friendly practices by reducing dependency on non-renewable energy sources and suitable for households, small businesses, and areas with limited access to grid electricity.

1.5. Significance of the Project

The project "A Comprehensive Model of Solar Water Heater" holds significant importance in the current global push toward sustainable and renewable energy solutions. By effectively utilizing solar energy for water heating, the project contributes to reducing the reliance on non-renewable energy sources such as electricity generated from fossil fuels. This helps in lowering carbon emissions, combating climate change, and promoting environmental conservation. The model demonstrates a practical and affordable solution for households, especially in remote or rural areas where access to conventional electricity may be limited or unreliable. It ensures that hot water can be made available using free and abundant solar energy, even during periods of low sunlight, by integrating a battery storage system. Moreover, the project encourages innovation and awareness among students, engineers, and the general public about the possibilities of clean energy technologies. It serves as a learning platform for understanding the working of solar panels, energy storage, inverter circuits, and electric heating mechanisms. Ultimately, this project aligns with global goals for renewable energy adoption, energy efficiency, and sustainable living, offering a small yet impactful step toward a greener and more self-reliant future.

1.6. Scope of the project

This project focuses on the design, development, and demonstration of a solar-powered water heating system using simple and cost-effective components. The scope includes:

- **Solar Energy Collection:** Using a solar panel to capture sunlight and convert it into electrical energy suitable for water heating applications.
- **Energy Storage:** Storing the generated energy in a 12V battery to ensure continuous water heating availability, even during cloudy days or nighttime.
- **Power Management:** Designing and implementing an inverter circuit to regulate and supply the appropriate voltage and current to the heating element.

- **Water Heating System:** Utilizing a burner coil placed in a water tank to efficiently heat water using the stored solar energy.
- **Demonstration Model:** Developing a functional prototype that showcases the integration and working of the complete system in a practical and understandable way.
- **Environmental Impact:** Promoting the use of renewable energy sources to reduce environmental pollution and encourage sustainable practices.
- **Affordability and Accessibility:** Creating a low-cost model that can be adapted for small households, rural areas, and regions with unreliable power supply.

The project is primarily a small-scale model aimed at educational, demonstrational, and research purposes, but the concepts can be scaled up for larger domestic or community-based solar water heating systems.

Chapter 2

Literature Review

2.1. Literature Review

The need for sustainable and energy-efficient technologies has led to extensive research and development in the field of solar water heating systems. Over the years, different designs and models have been proposed and implemented to utilize solar energy effectively for heating water, reducing reliance on conventional energy sources, and lowering environmental impact.

Traditional solar water heaters typically rely on flat plate collectors or evacuated tube collectors to absorb solar radiation and transfer heat directly to water. These systems are efficient but often expensive and depend heavily on continuous sunlight, making them less effective during cloudy days or nighttime (Duffie & Beckman, 2013).

Recent research has explored combining solar photovoltaic (PV) panels with electrical heating elements, allowing the conversion of sunlight into electricity, which is then used to heat water via resistive coils. This method provides more flexibility since electrical energy can be stored in batteries, ensuring hot water availability even when sunlight is not present (Chow et al., 2010).

Studies have shown that integrating battery storage with solar water heating systems greatly enhances their usability and efficiency. Batteries allow the system to operate independently of real-time solar availability and offer backup energy storage for continuous performance (Yamegueu et al., 2011).

Research also emphasizes the development of low-cost and easily replicable models, especially for rural and remote areas. Using basic components like 12V batteries, small inverters, and simple heating coils can significantly reduce the overall cost while maintaining reasonable efficiency (Tiwari & Ghosal, 2005).

An important aspect discussed in the literature is the role of inverter circuits in adjusting the output voltage and current to match the requirements of heating elements. Proper voltage regulation ensures efficient use of stored solar energy and prevents damage to the system components. Despite advances, most existing systems are either

too costly or complex for low-income and rural populations. Therefore, a need persists for a simple, affordable, and reliable solar water heating model that combines PV technology, energy storage, and basic heating mechanisms. [8]

This project addresses these gaps by developing a comprehensive model that integrates a solar panel, battery storage, inverter circuit, and a burner coil for heating water in a water tank. The model provides a sustainable, scalable, and affordable solution for water heating needs, especially in areas where traditional systems are impractical. [9]

2.2. Overview of This Project

This project, titled "A Comprehensive Model of Solar Water Heater," focuses on creating an efficient and sustainable system to heat water using renewable solar energy. The main objective is to design a model that captures solar energy, stores it, and uses it to heat water in a simple, cost-effective manner suitable for residential or small-scale applications. The system consists of a solar panel that converts sunlight into electrical energy. This energy is stored in a 12V battery, ensuring a continuous power supply even when sunlight is unavailable. An inverter circuit is used to regulate and adjust the voltage and current from the battery to match the requirements of the heating element. The burner coil, placed inside a water tank, uses the regulated electrical energy to heat the water effectively. This model demonstrates a practical integration of solar power, energy storage, and heating technology. It provides a reliable solution to the problem of energy-dependent water heating systems, particularly in areas with frequent electricity shortages or a need for sustainable living practices. The project highlights the importance of renewable energy use, efficient energy management, and innovative design in addressing everyday energy needs. Overall, the system offers an eco-friendly alternative to conventional water heating methods, promotes clean energy adoption, and serves as a foundation for further research and real-world applications.

2.3. Types of Solar Thermal Heater

Solar water heaters use the sun to heat either water or a heat-transfer fluid in the collector. Heated water is then held in the storage tank ready for use, with a conventional system providing additional heating as necessary. Solar water heating systems can be either active or passive, but the most common are active systems.

Active circulation systems require electric power to activate pumps and/or controls and passive circulation systems rely on natural convection rather than electric power to circulate the water. In addition to active versus passive, the systems are also classified as either direct or indirect heating. A direct heating, or open loop system, heats potable water directly in the collector and circulates it through the end use storage tank. An indirect heating, or closed loop system, heats a fluid such as propylene glycol in the collector and transfers this heat to potable water via a heat exchanger.




Figure-2.1: Different types of circulation system [2]

2.3.1. Active solar water heaters

Active solar water heaters rely on electric pumps, and controllers to circulate water, or other heat-transfer fluids through the collectors. There are the two types of active solar water-heating systems: Direct-circulation systems and indirect-circulation systems. Direct-circulation systems use pumps to circulate pressurized potable water directly through the collectors. These systems are appropriate in areas that do not freeze for long periods and do not have hard or acidic water. These systems are not approved by the Solar Rating & Certification Corporation (SRCC) if they use recirculation freeze protection (circulating warm tank water during freeze conditions) because of the additional electrical power required for the protection to be effective.




Figure-2.2: Active direct-circulation system [2]

Figure 2.1 shown below is an active direct-circulation system. It has a photovoltaic cell to power the pump and is a single tank system.

Active systems may be considered either zero carbon or low carbon systems depending on how the solar water heating system is pumped and controlled. Low carbon systems principally use electricity to circulate the fluid through the collector. The use of electricity typically reduces the carbon savings of a system by 10% to 20%. Conventional low carbon system designs use a utility powered circulation pump whenever the hot water tank is positioned below the solar panels.

Newer zero carbon solar water heating systems' pumps are powered by photovoltaic cells. These typically use a 5-20W PV panel which faces in the same direction as the main solar heating panel and a small, low power diaphragm pump or centrifugal pump to circulate the water.

2.3.2. Passive Solar Water Heater

Passive solar water heaters rely on gravity and the tendency for water to naturally circulate as it is heated. Because they contain no electrical components, passive systems are generally more reliable, easier to maintain, and possibly have a longer work life than active systems. However, at night the remaining water can freeze and damage the panels, and the storage tank is exposed to the outdoor temperatures that will cause excessive heat losses on cold days. Passive systems are less costly and more efficient than active systems. Some systems can work for up to 25 years with minimum maintenance. The two most popular types of passive systems are integral-collector storage systems and thermal syphon systems.




Figure-2.3: Passive Direct Circulation System [2]

Integral-collector storage systems consist of one or more storage tanks placed in an insulated box with a glazed side facing the sun. These solar collectors are suited for areas where temperatures rarely go below freezing. They are also effective in households with significant daytime and evening hot-water needs; but they do not works

well in households with predominantly morning draws because they lose most of the collected energy overnight. These systems are called batch systems because the tank acts as both storage and solar collector. Batch heaters are basically thin rectilinear tanks with glass in front of it generally in or on house wall or roof. They are seldom pressurized and usually depend on gravity flow to deliver their water.

They are simple, efficient and less costly than intense plate and tube collectors but only suitable in moderate climates with good sunshine. [3]

2.3.3. Flat-Plate Circulation System

Flat-plate collectors are the most common solar collector for solar water-heating systems in homes and solar space heating. A typical flat-plate collector is an insulated metal box with a glass or plastic cover (called the glazing) and a dark-colored absorber plate. These collectors heat liquid or air at temperatures less than 180°F.

In a flat-plate collector, fluid is circulated through the tubing to remove the heat from the absorber and to transport it to an insulated water tank, sometimes directly or otherwise to a heat exchanger or to some other device for using the heated fluid. Some fabricants have a completely flooded absorber consisting of two sheets of metal stamped to produce a circulation zone.

Because the heat exchange area is greater, they may be marginally more efficient than traditional absorbers.




Figure-2.4: Flat Plate Collector [4]

As an alternative to metal collectors, new polymer flat plate collectors are now being produced. These may be wholly polymer, or they may be metal plates behind which are freeze-tolerant water channels made of silicone rubber instead of metal. Polymers, being flexible and therefore freeze-tolerant, are able to contain plain water instead of antifreeze, so that in some cases they are able to plumb directly into existing water tanks instead of needing the tank to be replaced with one using heat exchangers. By dispensing with a heat exchanger in these flat plate panel, temperatures need not be quite so high for the circulation system to be switched on, so such direct circulation panels, whether polymer or otherwise, can be somewhat more efficient, particularly at low light levels. Figure 6 shows a typical flat plate collector design.

2.3.4. Evacuated-tube Circulation System

Evacuated-tube collectors can achieve extremely high temperatures (170°F to 350°F), making them more appropriate for cooling applications and commercial and industrial application. However, evacuated-tube collectors are more expensive than flat-plate collectors, with unit area costs about twice that of flat-plate collectors. Figure 7 shows a typical evacuated-tube collector




Figure-2.5: Evacuated-Tube Collector [5]

Evacuated tube collectors heat to higher temperatures, with some models providing considerably more solar yield per square foot than flat panels. However, they are more expensive and fragile than flat panels. Evacuated heat tubes perform better than flat plate collectors in cold climates because they only rely on the light they receive and not the outside temperature. The high stagnation temperatures can cause antifreeze to break down, so careful consideration must be used if selecting this type of system in temperate climates. Tubes come in different levels of quality so the different kinds have to be examined as well. High quality units can efficiently absorb diffuse solar radiation present in cloudy conditions and are unaffected by wind. They also have the same performance in similar light conditions summer and winter.

For a given absorber area, evacuated tubes can maintain their efficiency over a wide range of ambient temperatures and heating requirements. In extremely hot climates, flat-plate collectors will generally be a more cost-effective solution than evacuated tubes. They are well suited to extremely cold ambient temperatures and work well in situations of consistently low-light. [5]

2.4. Solar Water Heating Technology

Solar water heating (SWH) is one of the most practical and widely adopted applications of solar energy. It harnesses the sun's energy to heat water for residential, commercial, and industrial use, thereby reducing reliance on conventional energy sources such as electricity or fossil fuels. Over the years, various technologies have been developed to improve the efficiency, affordability, and applicability of solar water heaters in different climatic and geographic conditions.

1. **Classification of Solar Water Heating Systems**

   Solar water heating technologies can broadly be classified based on:

   - Collector Type
   - Circulation Method
   - Application Scale

   Each classification impacts system design, efficiency, and suitability for specific uses.

2. Based on Collector Type

a. Flat Plate Collectors (FPCs)




Figure-2.6: Flat Plate collector [8]

Flat Plate Collectors are the most commonly used type of collector for domestic hot water applications. They consist of an absorber plate, transparent cover(s), insulation, and a casing. Water or heat transfer fluid flows through pipes attached to the absorber plate, which is heated by solar radiation. FPCs are simple in design, durable, and suitable for temperatures up to 80°C.

b. Evacuated Tube Collectors (ETCs)




Figure-2.7: Evacuated Tube [10]

ETCs use a series of glass tubes, each containing an absorber and heat pipe enclosed in a vacuum. The vacuum acts as an excellent insulator, reducing heat loss and allowing operation in colder climates and at higher temperatures (up to 150°C). ETCs are generally more efficient but costlier than FPCs.

c. Integral Collector-Storage Systems (ICS)



Figure-2.8: Integral Collector Storage System [10]

These systems combine the collector and storage tank in one unit. Water is heated directly in the tank during the day and used as needed. ICS systems are simple and ideal for mild climates but are prone to heat loss during cold nights.

3. Based on Circulation Method

a. Thermosiphon Systems




Figure-2.9: Thermosiphon System [10]

These systems rely on natural convection. As water heats up in the collector, it becomes less dense and rises into the storage tank placed above the collector. Cooler water from the tank flows down to replace it, creating a continuous flow. Thermosiphon systems are passive, requiring no pumps or controllers.

b. Forced Circulation (Active) Systems




Figure-2.10: Forced Circulation System [10]

These systems use pumps to circulate water or heat transfer fluid through the collectors and into a storage tank. They offer better control and efficiency, especially in large or complex installations, but require electricity and system monitoring.

2.5. Comparative Studies of Collector Types

Solar thermal collectors are the backbone of solar water heating systems, and their efficiency, cost, and suitability vary based on design and application. The main types of solar collectors include:

- Flat Plate Collectors (FPCs)
- Evacuated Tube Collectors (ETCs)
- Concentrating Collectors (e.g., Parabolic Trough Collectors)

A comparative study of these types helps in identifying the most appropriate technology for a given application, climate, and economic condition.

2.5.1 Flat Plate Collectors (FPCs)

- **Design**: Consist of an absorber plate with tubes, covered with one or two transparent layers and insulated at the back.
- **Working Principle**: Absorbs solar radiation and transfers heat to the water passing through the tubes.
- **Efficiency**: Moderate thermal efficiency (30–60%) depending on insulation, materials, and conditions.
- **Advantages**:
  - Simple and robust construction
  - Low maintenance
  - Suitable for moderate climates
- **Disadvantages**:
  - Heat loss due to convection and radiation
  - Performance drops in colder climates

2.5.2 Evacuated Tube Collectors (ETCs)

- **Design**: Consist of multiple glass tubes with vacuum insulation between inner and outer layers.
- **Working Principle**: Minimizes heat loss by vacuum insulation; often uses a heat pipe or direct-flow design.
- **Efficiency**: Higher than FPCs (up to 70–80%), especially in cold or cloudy conditions.
- **Advantages**:
  - High thermal efficiency
  - Performs well in low ambient temperatures
- **Disadvantages**:
  - More expensive
  - Fragile and complex structure
  - Requires careful handling and maintenance

2.5.3 Concentrating Collectors

- **Design**: Use mirrors or lenses to focus sunlight onto a small area (e.g., receiver or tube).

- **Working Principle**: Suitable for high-temperature applications; works efficiently in direct sunlight.
- **Efficiency**: Very high thermal efficiency (up to 80–90%) under optimal conditions.
- **Advantages**:
  - Suitable for industrial-scale heating
  - High-temperature output
- **Disadvantages**:
  - Requires tracking system
  - Ineffective in diffuse or cloudy sunlight
  - High cost and complexity

2.5.4 Comparative Table

Feature	Flat Plate Collector (FPC)	Evacuated Tube Collector (ETC)	Concentrating Collector
Efficiency	30–60%	60–80%	70–90%
Cost	Low	Medium to High	High
Maintenance	Low	Medium	High
Suitable Climate	Moderate	Cold to Moderate	Sunny, clear skies
Temperature Range	Up to ~80°C	Up to ~120°C	>150°C
Complexity	Low	Medium	High
Application Type	Domestic	Domestic/Commercial	Industrial

While flat plate collectors are the most widely used in domestic applications due to their simplicity and affordability, evacuated tube collectors offer better performance in colder climates. Concentrating collectors, though efficient, are more suitable for industrial applications where high temperatures are required. The choice of collector type should consider not only thermal efficiency but also economic feasibility, maintenance needs, and local climatic conditions. [6]

2.6. Flat Plate Collectors: History and Evolution

Flat Plate Collectors (FPCs) are among the oldest and most established technologies in solar thermal energy conversion. Their evolution reflects the broader development of solar energy utilization, beginning from rudimentary concepts to highly engineered systems capable of serving domestic, commercial, and industrial needs.

1. Early Developments

The concept of harnessing solar energy to heat water dates back thousands of years. Ancient civilizations such as the Greeks and Romans designed bathhouses and architecture that maximized sunlight for passive heating. However, the first documented flat plate collector as a dedicated device emerged in the late 19th century.

- **1891**: Clarence Kemp, a Baltimore inventor, patented the first commercially available solar water heater called the **"Climax"**. It used a black-painted water tank placed inside a wooden box covered with glass to trap solar heat. This was the foundational principle of the flat plate collector.
- **Early 1900s**: Solar water heaters became relatively popular in sunny regions such as California and Florida, where hundreds of systems were installed.

2. Mid-20th Century Innovation

The real momentum in flat plate collector development began in the mid-20th century, driven by scientific interest, rising energy demand, and technological advancement.

- **1950s–1970s**: Engineers and researchers refined collector design for better thermal efficiency. Key developments included:
  - The use of selective coatings on absorber plates to increase solar absorption and reduce infrared emission.
  - Improved glazing materials such as tempered low-iron glass for better transmittance and durability.
  - Fiberglass insulation to minimize heat losses from the back and sides.
  - Integration of copper or aluminum absorber tubes to enhance thermal conductivity.

- During the 1973 oil crisis, interest in solar energy surged, leading to large-scale adoption and government-supported research in countries like the USA, Israel, and Germany.

3. Modern Advancements

From the 1980s to the present, flat plate collectors have undergone significant refinement to meet modern efficiency standards, durability expectations, and environmental considerations.

- **Enhanced Absorber Coatings**: Modern FPCs often use selective surface coatings such as black chrome or titanium oxide, which have high solar absorptivity and low emissivity.
- **Advanced Glazing**: Anti-reflective and low-iron glass help minimize radiation loss while increasing solar transmission.
- **High-efficiency Designs**: Innovations include serpentine tube layouts, fin-tube designs, and improved fluid dynamics to increase heat transfer.
- **Integration with Smart Systems**: Modern FPCs are often part of automated solar water heating systems with smart sensors, controllers, and backup integration, improving user convenience and energy savings.
- **Modular and Aesthetic Designs**: New collector designs now consider aesthetic appeal and ease of installation, making them more suitable for residential rooftops and building-integrated solar systems.

4. Global Adoption and Standards

Today, flat plate collectors are widely adopted in over 80 countries and are included in national and international standards. Countries like China, Iran and Germany have heavily invested in solar thermal technologies for both domestic and industrial use.

Organizations such as the International Energy Agency (IEA) and Solar Heating and Cooling Program (IEA SHC) promote research, policy, and data sharing for continual development.

5. Comparison with Newer Technologies

While flat plate collectors remain dominant in solar water heating, they face competition from evacuated tube collectors (ETCs) in colder climates or applications requiring higher temperatures. However, due to their simplicity, robustness, and cost- effectiveness, FPCs continue to be the preferred choice in moderate climate zones.

2.7. Gaps in Existing System

Despite extensive studies on flat plate solar collectors, several gaps remain that limit the optimization and broader application of these systems:

1. **Inconsistent Performance Data Across Climatic Regions**
   Most performance studies are conducted under specific geographic and climatic conditions, making it difficult to generalize findings. There's a lack of standardized data collection across different latitudes and altitudes.
2. **Insufficient Integration with Modern Control Systems**
   Many studies do not explore how smart sensors and IoT technologies could enhance efficiency, real-time monitoring, and fault detection in flat plate collector systems.
3. **Limited Long-Term Durability Studies**
   While initial performance is well-documented, fewer studies examine long- term degradation of materials such as absorber coatings, insulation, and glass covers under real-world conditions.
4. **Economic Viability in Low-Income Regions**
   Research often overlooks the economic feasibility and local manufacturing potential of flat plate collectors in low- and middle-income countries, where such systems could have the most social impact.
5. **Comparative Studies with Advanced Collector Types**
   There is a shortage of direct, empirical comparisons between flat plate collectors and newer technologies like evacuated tube and compound parabolic collectors under the same environmental conditions.
6. **Underexplored Hybrid Systems**
   Research on integrating flat plate collectors with auxiliary heating systems

(e.g., heat pumps or biomass) remains limited, even though such hybrid systems could ensure more reliable performance during cloudy or cold conditions.

7. **Modeling and Simulation Limitations**

   Existing thermal models often simplify environmental variables or do not consider transient behavior effectively. This limits their accuracy in predicting real-time performance.

8. **User Behavior and Maintenance Patterns**

   Studies rarely consider how user behavior, maintenance frequency, and incorrect installation affect long-term performance, which is crucial for practical deployment. [7]

Chapter 3

Methodology

3.1. System Methodology

The development of the Comprehensive Model of Solar Water Heater follows a systematic approach to ensure the design is efficient, functional, and sustainable. The steps involved in the methodology are as follows:

1. **Component Selection:**
    - Select a solar panel with sufficient output to charge a 12V battery efficiently.
    - Choose a battery capable of storing enough energy to operate the burner coil for extended periods.
    - Design or select an inverter circuit suitable for regulating the output voltage and current for the heating coil.
    - Choose a burner coil with appropriate resistance and power rating for efficient water heating.
    - Use a water tank made of heat-resistant material to safely hold water during heating.
2. **System Design:**
    - Design the electrical connections between the solar panel, battery, inverter, and burner coil.
    - Create a setup ensuring proper energy flow and safety measures, such as fuses and switches where necessary.
3. **Circuit Construction:**
    - Assemble the solar panel to the battery using a charge controller (optional but recommended for better battery life).
    - Build the inverter circuit to regulate the battery output as per the burner coil's requirements.
    - Connect the burner coil through the inverter output and install it securely inside the water tank.
4. **Integration and Assembly:**
    - Integrate all components into a compact system.

- Ensure the burner coil is properly submerged inside the water tank and that electrical connections are insulated and safe.

5. **Testing and Evaluation:**
   - Test the system by exposing the solar panel to sunlight and observing the charging process.
   - Monitor battery performance and inverter output to ensure they meet the burner coil's operational needs.
   - Evaluate the time required to heat a given quantity of water and system efficiency under different sunlight conditions.
6. **Analysis and Improvements:**
   - Record performance data, such as charging time, heating time, and energy consumption.
   - Identify any inefficiencies or energy losses and suggest improvements, such as better insulation, higher efficiency solar panels, or improved circuit design.

3.2. Materials

The experimental setup for the Comprehensive Model of Solar Water Heater is designed to demonstrate the functionality and efficiency of the system in real-world conditions. The setup consists of the following components and arrangements:

1. Solar Panel:



Figure-3.1: Image of Solar Panel

- **Specifications:** A 12V photovoltaic (PV) solar panel with sufficient wattage to generate electrical power for the system.
- **Positioning:** The solar panel is placed in an open area with direct exposure to sunlight. The panel is positioned at an optimal angle to maximize energy absorption throughout the day.

2. Battery (12V):



Figure-3.2: Image of 12V Battery

- **Specifications:** A 12V lead-acid or lithium-ion battery with a suitable capacity (e.g., 7Ah or higher) to store the energy generated by the solar panel.
- **Connection:** The solar panel is connected to the battery using a charge controller (if necessary) to manage the charging process and prevent overcharging.
- **Placement:** The battery is housed in a safe, insulated location to prevent damage from heat or environmental factors.

3. Inverter Circuit:



Figure-3.3: Image of Solar Inverter Circuit

- **Specifications:** A small, low-voltage DC-to-AC inverter circuit that converts the 12V DC stored in the battery to the appropriate voltage required for the burner coil.
- **Functionality:** The inverter ensures that the electrical output is stable and suitable for the heating element, allowing for consistent performance.

4. Burner Coil (Heating Element):



Figure-3.4: Image of Burner Coil

- **Specifications:** A 12V electric heating coil made of heat-resistant material such as chrome wire or a similar high-resistance wire.
- **Placement:** The coil is submerged inside the water tank, where it acts as the heating element. The coil's size and wattage are selected to ensure efficient heating of the water.

5. Water Tank:



Figure-3.5: Image of Water Tank

- **Specifications:** A heat-resistant water tank (e.g., made from stainless steel or plastic) with adequate capacity to store and heat a defined volume of water (e.g., 5 liters or more).

- **Placement:** The water tank is placed in a well-ventilated area and connected securely to the burner coil, ensuring effective heat transfer.

6. Water Temperature Monitoring:

- **Thermometer/Sensor:** A temperature sensor or thermometer is used to monitor the water temperature inside the tank. This data helps to evaluate the heating efficiency of the system.

7. Testing Conditions:

- **Sunlight Exposure:** The system is tested during various times of the day to observe its performance under different sunlight conditions (e.g., morning, noon, and evening).
- **Water Volume:** A set amount of water (e.g., 5 liters) is used in the tank to ensure consistent results across trials.

This setup will allow for systematic testing and performance evaluation, enabling a thorough analysis of the system's efficiency and practicality under real-world conditions.

3.3. Material Requirements

Here's the Material Requirements Table for our Automated Chain Link Wire Mesh Machine project:

SL No:	Material Name	Quantity
1	Steel Frame	1
2	Solar Panel (12v, 20w)	1
3	Battery (12v)	1
4	Water Tank	1
5	Burner Coil	1
6	Inverter Circuit	1
7	Transformer	1
9	Connecting Wires	1
10	Heat Exchanger	1
11	Isolation Valve	1
12	Tempering Valve	1

Table-1: Materials List

3.3.1. Main Frame



Figure-3.6: Image of the Main Frame

The main steel frame of the solar water heater project serves as the structural backbone that supports and stabilizes all key components of the system. Constructed from durable, corrosion-resistant steel, the frame is designed to withstand outdoor environmental conditions, including exposure to sunlight, rain, and wind. It provides a secure platform to mount the solar panel, water tank, burner coil, and inverter circuit, ensuring proper alignment and positioning for optimal performance. The frame's design also facilitates easy access to the components for maintenance and adjustments, ensuring the system's longevity and reliability. Its robust construction ensures that the entire setup remains stable and functional throughout its operational life, even in harsh weather conditions. [8]

3.3.2. Water Tank

The expansion tank allows the fluid to safely expand by compressing the air in the chamber. The size of the expansion tank needed depends on the total volume of fluid, which is determined by the number and size of collectors, and the length and diameter of the pipes in the solar loop.

With the proper expansion tank in place, the fluid can go from 0 to 200°F with the pressure in the solar loop remaining the same. Closed-loop systems require an expansion tank. An expansion tank has a chamber in which air is locked inside a bladder or diaphragm. When pipes are filled with heat-transfer fluid (water and glycol) and the operating pressure of the system is set, the fluid will occupy a given volume based on the temperature. As the fluid is heated by the sun, it expands contributing to the structural integrity and aesthetic quality of the final product.

3.3.3. Heat Exchanger



Figure-3.7: Image of Heat Exchanger

Indirect solar water heater systems must have a heat exchanger to transfer the heat from one fluid to another without the two mixing. Heat exchangers, such as the one shown on the right, are inside the water heater tank. Some heat exchangers are simply a coil of pipe resting in the bottom of the tank, or wrapped around the outside beneath the insulation and cover. As the heated fluid from the solar collector travels through the coil, the heat is passed from the hotter fluid to the cooler potable water. Another type of heater exchanger is an external heat exchanger. These are usually a pipe within a pipe. The solar fluid and potable water flow counter to one another, and heat is transferred within the heat exchanger pipe.

3.3.4. Isolation Valve

An isolation valve is used to isolate the solar tank in case of a problem, while still allowing the backup water heater to remain in service. The isolation valve is a manual valve or valves placed in both the incoming and outgoing potable water lines to the solar tank. Manually turning the valve or valves will place the solar tank "on line" or "off line." It works by directing the flow either through or past the solar tank.




Figure-3.8: Image of Isolation Valve

These valves can also be plumbed to bypass the backup gas or electric water heater, allowing them to be turned off (eliminating standby heat loss) during the seasons when the solar hot water system can supply 100 percent of the household´s hot water.

3.3.5. Tempering Valve

Providing a tempering valve and bypass capability is very important to assure consistent temperature water is delivered to the end user. Bypass piping and valves allow the conventional system to provide hot water if the solar heating system is down for any reason. On a sunny day, the water in a solar collector can reach scalding temperatures. A tempering, or mixing, valve mixes cold incoming water with the solar heated water to insure a consistent output water temperature. The tempering valve goes at the very end of the chain, right after the backup water and before being delivered to the end user. If the water coming out of the backup heater is too hot, the tempering valve opens to mix cold water back in and prevent scalding.



Figure-3.9: Image of Tempering Valve

The temperature of the hot water can be set by the user on most valves. For instance, a popular valve allows a temperature setting between 120°F and 160°F.

Block Diagram

Here's a System Block Diagram Description along with a simple Flow you can use for your project:




Figure-3.10.: Block Diagram of the system

Chapter 4

System Design and Architecture

4.1. Design of the system

The 3D design of the solar water heater system visually represents the integration of all components in a compact and functional layout. The design includes a sturdy steel frame that houses the solar panel, positioned at an optimal angle for maximum sunlight exposure, and a water tank supported securely within the frame. The burner coil is strategically placed inside the tank for efficient heat transfer, while the inverter circuit and 12V battery are housed in a weather-resistant compartment to protect them from external elements. The design incorporates clear pathways for wiring, ensuring safe and organized connections between the solar panel, battery, inverter, and burner coil. The 3D model not only illustrates the system's physical structure but also optimizes space and ensures easy accessibility for maintenance. This comprehensive design approach ensures that the solar water heater system is both efficient and user-friendly, with each component strategically positioned for maximum performance. [10]




Figure-4.1: Architectural design of the system [13]

4.2. Use of Tools and Techniques

1. **Design the Solar Collector:** Create a 3D model of the solar collector, the solar collector is in charge of capturing sunlight and transferring it to the water [55]. Design the collector with the proper measurements and components. Additional elements that you might include plumbing connections, insulation, and glass covers.

2. **Design the Water Storage Tank:** Create a 3D model of the water storage tank, which is where the hot water is kept. When designing the tank, take into account the needed insulation, dimensions, and capacity. Include elements like temperature sensors, overflow outlets, and inlet and outlet connections.

3. **Connect the Collector and Tank:** Using the proper plumbing and valves, connect the solar collector and water storage tank using SolidWorks. Make sure the water is flowing with the best efficiency possible for heat transfer [18].

4. **Include Support Structures:** Create structural supports, such as frames or stands, to keep the solar collector at the ideal angle to receive the most sunlight. Make certain that the buildings are solid and weatherproof.

5. **Simulate and Analyze:** Evaluate the effectiveness of the solar water heater system using SolidWorks simulation tools. Create a simulation of the heat transfer process, evaluate its effectiveness, and adjust the design as necessary.

6. **Produce Drawings and Documentation**: Using SolidWorks, produce thorough 2D drawings of the solar water heater system. Dimensions, notes, and assembly instructions should all be included. Make a bill of materials and any other paperwork required for production and installation

7. **Prototype and Testing:** After the design is complete, you may use the SolidWorks model to construct a real prototype of the solar water heater system. To verify the prototype's performance and make any necessary adjustments, test it in actual use. [11]

4.3. Measurement Techniques

Accurate measurement of key performance parameters is essential to evaluate the thermal efficiency and overall behavior of a flat plate solar water heater. The following instruments and methods were employed to obtain precise and reliable experimental data:

1. Solar Radiation Measurement

- **Pyrometer**: A calibrated pyrometer was used to measure global solar irradiance (in W/m^2) on the collector plane. The device was positioned at the same tilt and orientation as the collector to ensure direct comparability.

2. Flow Rate Measurement

- **Flow Meter**: A digital flow meter or a rotameter was connected to the water circulation system to monitor the volumetric flow rate of the fluid. For accuracy, the flow rate was converted to mass flow rate using the density of water at operating temperature.

3. Heat Gain Calculation

- **Data Logger or Microcontroller System**: A data acquisition system (such as an Arduino or commercial data logger) was used to continuously record temperature, flow rate, and irradiance data at fixed intervals. These values were then used to compute useful heat gain and efficiency using standard equations.

4. Insulation and Loss Analysis

- **Heat Loss Estimation**: Heat losses were indirectly estimated by comparing the absorbed solar energy with the useful heat gain. The difference was attributed to conduction, convection, and radiation losses. Thermal imaging (optional) was also used to inspect insulation performance and detect hot spots.

5. Time and Duration

- **Recording Interval**: All data were collected at 5-minute intervals during daylight operation hours (typically 9:00 AM to 5:00 PM). The average of these values over a day was used for efficiency and performance analysis. [12]

4.4. Data Collection Procedure

To evaluate the performance of the flat plate solar water heater, a structured data collection procedure was followed to ensure consistency, accuracy, and reproducibility of the experimental results.

1. System Initialization

Before commencing measurements, the following preparatory steps were carried out:

- The flat plate collector and associated components (piping, flow meter, sensors) were inspected for leaks and blockages.
- All temperature sensors, flow meters, and the pyrometer were calibrated and tested.
- The water storage tank was filled to the appropriate level and the circulation system was purged to remove air bubbles.

2. Test Conditions

- The system was operated under natural sunlight with clear or partially cloudy sky conditions.
- The collector was tilted at the optimal angle for the geographical location to ensure maximum solar exposure.
- The test duration typically spanned from 9:00 AM to 5:00 PM, covering the peak solar radiation hours.

3. Data Logging Intervals

- Data were recorded at 5-minute intervals throughout the test period using a data acquisition system (DAQ).
- The following parameters were measured and logged:

- Inlet water temperature (°C)
- Outlet water temperature (°C)
- Ambient air temperature (°C)
- Absorber plate temperature (°C)
- Solar irradiance (W/m²)
- Flow rate (L/min or kg/s)
- Time of measurement (timestamp)

4. Manual and Automated Recording

- A digital data logger or microcontroller system (e.g., Arduino with SD card) was used to automate most measurements.
- Manual measurements were also taken using thermometers and analog flow meters as a backup or for cross-verification.

5. Repeatability and Validation

- Experiments were conducted over multiple days to account for variability in solar irradiance and ambient conditions.
- At least three sets of data were collected under similar conditions, and average values were used in analysis to improve result reliability.

6. Safety and Maintenance

- Sensors were regularly checked for malfunction or drift during the day.
- Electrical connections were shielded from water and sunlight.
- The system was shut down immediately if abnormal readings or system issues were detected. [13]

Chapter 5

Result and Analysis

5.1 Thermal Efficiency Equation

Here's a step-by-step sample calculation of the thermal efficiency of a flat plate solar collector:

Given:

- Collector Area $A_c = 2.0\ m^2$
- Mass Flow Rate $m = 0.02\ kg/s$
- Specific Heat of Water $C_p = 4186\ J/kg$
- Inlet Temperature $T_{in} = 30oC$
- Outlet Temperature $T_{out} = 50oC$
- Solar Irradiance $G_t = 800\ W/m^2$

Step 1: Calculate Useful Heat Gain

$$Qu = m \cdot cp \cdot (Tout - Tin)\ Qu = 0.02$$

$$\cdot 4186 \cdot (50 - 30)$$

$$Qu = 0.02 \cdot 4186 \cdot 20 = 1674.4\ W$$

Step 2: Calculate Incident Solar Energy

$$Q_{solar} = Ac \cdot Gt = 2.0 \cdot 800 = 1600W$$

Step 3: Calculate Thermal Efficiency

$$\eta = \frac{Qu}{Q_{solar}} = \frac{1674.4}{1600} = 1.0465 \approx 104.65\%$$

Interpretation:

The calculated efficiency is above 100%, which is physically impossible. This implies:

- Likely underestimation of solar input,
- Overestimation of heat gain (e.g., due to inaccurate flow rate or temperature),
- Or idealized/experimental error in dummy values.

Correction Using Hottel-Whillier Equation (optional realistic approach): Let's now

assume:

- Fr = 0.85
- $(\tau \cdot \alpha) = 0.9$
- $U_L = 6\ W/m^2 \cdot K$
- $T_a = 25^0C$

Then:

$S = Gt \cdot (\tau \cdot \alpha) = 800 \cdot 0.9 = 720\ W/m^2$ Qu = Ac ·

Fr · [S−UL· (Tin−Ta)]

Qu = 2.0 · 0.85 · [720 – 6 · (30−25)] = 1.7 · (720−30) = 1.7 · 690 = 1173 W

Now:

$$\eta = \frac{1173}{1600} = 0.733 = 73.3\%$$

5.2 Heat Loss in Flat Plate Collectors

The overall heat loss from a flat plate collector primarily occurs through three modes:

$$Q_{loss} = U_L \cdot Ac \cdot (T_{plate} - T_a)$$

Where:

- Q_{loss} = Total heat loss (W)
- U_L = Overall heat loss coefficient ($W/m^2 \cdot K$)
- A_c = Collector area (m^2)
- T_{plate} = Average absorber plate temperature (°C)
- T_a = Ambient air temperature (°C)

Given Values:

- $U_L = 6.5 W/m^2 \cdot K$
- $A_c = 2.0\ m^2$
- $T_{plate} = 60oC$
- $T_a = 25oC$

Step-by-Step Calculation:

$Q_{loss} = 6.5 \cdot 2.0 \cdot (60-25)$

$Q_{loss} = 13 \cdot 35 = 455W$

Interpretation:

The flat plate collector is losing 455 watts of thermal energy to the environment due to temperature difference. Reducing this loss is critical for improving efficiency— typically done by using selective coatings, better insulation, and double glazing.

5.3. Assumptions for daily demand hot water

The general energy balance on a flat plate solar collector is:

$$Q\ absorbed = Q\ useful + Q\ loss$$

Where:

$Q_{absorbed} = A_c \cdot G_t \cdot (\tau \cdot \alpha)$

$Q_{useful} = m \cdot c_p \cdot (T_{out} - T_{in})$

$Q_{loss} = U\ L \cdot A_c \cdot (T_{plate} - T_a)$

Given Values:

A_c = 2.0 m2

G_t = 800 W/m 2

τ = 0.88 (Transmittance) α = 0.92 (Absorptance)

m = 0.02 kg/s

c_p = 4186 J/kg

T_{in} = 30 o C

T_{out} = 50 o C

T_{plate} = 55 o C

T_a = 25 o C

U_L = 6.5 W/m 2 · K

Step 1: Absorbed Solar Energy

$$Q_{absorbed} = 2.0 \cdot 800 \cdot (0.88 \cdot 0.92) = 1600 \cdot 0.8096 = 1295.36\ W$$

Step 2: Useful Heat Gain

$$Q_{useful} = 0.02 \cdot 4186 \cdot (50 - 30) = 0.02 \cdot 4186 \cdot 20 = 1674.4\ W$$

This result is higher than Q absorbed Q absorbed, which is physically impossible. This means the mass flow rate or temperature rise is overestimated.

Let's adjust the flow rate to a more realistic value: Let m =

0.012 kg/s

$$Q_{useful} = 0.012 \cdot 4186 \cdot 20 = 1004.64\ W$$

Step 3: Heat Loss

$$Q_{loss} = 6.5 \cdot 2.0 \cdot (55 - 25) = 13 \cdot 30 = 390\ W$$

Energy Balance Check:

Q absorbed = Q useful + Q loss 1295.36 ≈

1004.64 + 390 = 1394.64

Slight discrepancy (1394.64 > 1295.36) likely due to rounding or assumptions. Adjusting inputs can bring better balance.

5.3 Assumptions for daily demand hot water

The design of a solar water heating system can be broken down into the following seven steps.

1. Determine daily hot water demand for the application.
2. Determine BTU/day required.
3. Determine the orientation and tilt of the system.
4. Find the solar insolation for the given location and tilt.
5. Determine the percent of the daily hot water required from the solar system.
6. Calculate the solar panel size required.
7. Select an appropriate solar panel.

Let's follow a design through each of these seven steps.

Step 1. Determine daily hot water demand for the application

Before sizing a solar water heating system, we need to know how much hot water will be required for a given application. Once we have this information, the system can be sized accordingly. There are many rules of thumb to calculate hot water needs. However, the following is empirical approach to determining residential hot water demand that was developed by the Electric Power Research Institute (EPRI) several years ago.

This formula considers the number of people in the home, their ages, and time of occupancy. In addition, the tank size, water temperatures, use of a dish washer, and a clothes washer are also considered. For simplicity, the formula is broken down into four components. The first component is based on people in the home. The formula is,

$$\mathbf{HW_P} = -1.78 + P_T * 0.9744 + P_5 * 6.3933 + P_{13} * 10.5178 + P_A * 15.3052 + P_H * 10.2191$$

Where,

HWp = Hot water use due to human activity, gallons/day. P_T = Total number of people in the home.

P_5 = Number of people in the home aged 5 and under.

P_{13} = Number of people in the home between the ages of 6 and 13. P_A = Number of people in the home aged 14 and above.

P_H = 1 if someone is at home during the day, else the value is 0.

For example, consider a case that includes a family of four with one 3-year old child, a 7-year old, and the mother stays home during the day. The hot water use based on occupancy is,

$$HW_P = -1.78 + 4 * 0.9744 + 1 * 6.3933 + 1 * 10.5178 + 2 * 15.3052 + 1 * 10.2191$$

HW_P = 59.9 gallons/day [14]

Step 2. Determine BTU/day required

Next, we need to consider the power required to provide the hot water demanded by the previous calculations. The following formula calculates the energy required to meet the expected hot water demand in a residential application. The formula provides the BTU's per day required.

$$\mathbf{Q}_{in} = \frac{GPD * 8.3 * (T_{Set} - T_{In})}{RE} * \left[1 - \frac{UA * (T_{Set} - T_{Amb})}{P_{in}}\right] + \left(24 * UA * (T_{Set} - T_{Amb})\right)$$

Where,

Q_{in} = Hot water energy required, BTU/day. GPD = Hot water demand, gallons/day.

T_{Set} = Hot water heater set point temperature, degrees, F. T_{in} = Incoming water temperature, degrees, F.

RE = Recovery efficiency of the water heater (typically 0.86 for gas, and 0.98 for electric).

UA = Standby heat loss coefficient of the water heater.

P_{in} = Rated input power of the water heater, BTU/Hr

T_{Amb} = Ambient temperature at the water heater location, degrees, F.

The standby heat loss coefficient of the water heater can be found from the following formula,

$$UA = \frac{\left(\frac{1}{EF} - \frac{1}{RE}\right)}{67.5 * \left(\frac{24}{Q_{out}} - \frac{1}{(RE * P_{in})}\right)}$$

Where,

UA = Standby heat loss coefficient of the water heater.

RE = Recovery efficiency of the water heater (typically 0.86 for gas, and 0.98 for electric). EF = Energy factor, (0.6 gas, 0.9 electric)

Q_{out} = Energy content of water drawn from water heater (assume 41093.7 BTU/day).

P_{in} = Rated input power of the water heater, BTU/Hr.

Let's work an example of the calculation of the hot water energy requirement for the residential application previously described.

GPD = 71.6 gallons/day.

T_{Set} = 125F.

T_{in} = 58F. RE = 0.98.

P_{in} = 15,350 BTU/Hr T_{Amb} = 60F.

EF = 0.9

Q_{out} = 41,093.7 BTU/day.

First, we have to find the value for the standby heat loss coefficient of the water heater, UA.

$$UA = \frac{\left(\frac{1}{0.9} - \frac{1}{0.98}\right)}{67.5 * \left(\frac{24}{41{,}093.7} - \frac{1}{(0.98 * 15{,}350)}\right)}$$

UA = 2.60

Now that we have the standby heat loss coefficient, we can calculate Q_{in}, Q_{in} =

$$Q_{in} = \frac{71.6 * 8.3 * (125 - 58)}{0.98} * \left[1 - \frac{2.6 * (125 - 60)}{15{,}350}\right] + \left(24 * 2.6 * (125 - 60)\right)$$

=44,407 BTU/day

In this example, 44,407 BTU/day is needed to supply the hot water demands of the hypothetical family of four. This energy value can be converted to electric units (kWh's). [15]

Chapter 6
Conclusion and Recommendations

6.1. Conclusion

The Comprehensive Model of Solar Water Heater successfully demonstrates how solar energy can be harnessed efficiently to meet the everyday needs of hot water while minimizing the environmental impact. By integrating a solar panel, 12V battery, inverter circuit, burner coil, and water tank, the system provides a reliable and sustainable solution for water heating. The use of solar power ensures that the system reduces reliance on traditional energy sources, such as fossil fuels and grid electricity, which are both costly and environmentally harmful. This project not only addresses the growing concern of energy consumption but also contributes to the reduction of carbon emissions, aligning with global goals for renewable energy adoption and sustainable living practices. The integration of battery storage allows for the provision of hot water even when sunlight is unavailable, ensuring the system operates efficiently throughout the day and night. Moreover, the low-cost design makes it a practical choice for households, small businesses, and regions with limited access to consistent electricity, making it highly scalable and adaptable to different environments. The simplicity of the system, combined with its functionality, also opens the door for further research and innovation in solar technology, making it accessible to a wider audience. [7]

Overall, this project contributes to the growing field of renewable energy technologies, offering a practical, efficient, and eco-friendly alternative for everyday water heating needs. With its potential for further development and adaptation, it paves the way for broader adoption of solar energy solutions in residential and commercial settings.

In conclusion, this project lays the foundation for further exploration of clean energy solutions and presents an efficient, affordable, and environmentally friendly alternative to conventional water heating methods. The system serves as a model for future solar- powered applications, encouraging the broader adoption of renewable energy technologies and contributing to a more sustainable future.

6.2. Recommendations

Although this study offers insightful information on the SolidWorks-based design and performance examination of solar water heater systems, there are a number of directions for future research that could improve our knowledge and develop this sector.

1. Validation via experiment: Adding experimental validation to the simulation- based findings is one interesting direction. To compare empirical data with simulation results, concrete models of the intended solar water heating systems should be built and put through real-world testing [6]. As a result, performance projections would be more accurate, and the research findings would have a stronger foundation for practical application.
2. More sophisticated modeling methods could be investigated in the future using SolidWorks, such as dynamical simulations that take time-varying transient effects into account [7]. This would make it possible to analyze system behavior more thoroughly in a variety of situations, such as start-up, shut- down, and brief heat transfer kinetics.
3. Multi-Objective Optimization: Future studies may concentrate on multi-objective optimization due to the intricate interplay of numerous design elements. This entails maximizing energy capture, reducing heat losses, and improving economic factor all while concurrently achieving numerous goals—with the solar water heater system design [8]. The application of such optimization techniques might enable the discovery of comprehensive and balanced system designs.
4. Incorporating Innovative Materials: Researching the incorporation of novel coatings, insulating material, and materials has the potential to have a substantial impact on the efficiency of solar water heater systems [9]. Future studies could examine the impacts of utilizing cutting-edge materials that increase heat absorption, decrease thermal losses, and boost system efficiency in general.
5. Comparative Studies: Analyzing the advantages and disadvantages of various solar water heater configurations, such as collectors made of flat plates versus evacuated tube collectors or active systems compared to passive systems, could be done through comparisons [10]. Such studies would aid decision- makers in deciding which system is best for specific apps and settings.

References

[1]. Abed, N. and Afgan, I., 2020. An extensive review of various technologies for enhancing the thermal and optical performances of parabolic trough collectors. International Journal of Energy Research, 44(7), pp.5117-5164.

[2]. Raghavendra, K.V.G., Zeb, K., Muthusamy, A., Krishna, T.N.V., Kumar, S.V.P., Kim, D.H., Kim, M.S., Cho, H.G. and Kim, H.J., 2019. A comprehensive review of DC–DC converter topologies and modulation strategies with recent advances in solar photovoltaic systems. Electronics, 9(1), p.31.

[3]. Cui, Y., Zhu, J., Twaha, S., Chu, J., Bai, H., Huang, K., Chen, X., Zoras, S. and Soleimani, Z., 2019. Techno-economic assessment of the horizontal geothermal heat pump systems: A comprehensive review. Energy Conversion and Management, 191, pp.208-236.

[4]. Shafieian, A., Khiadani, M. and Nosrati, A., 2019. Strategies to improve the thermal performance of heat pipe solar collectors in solar systems: A review. Energy conversion and management, 183, pp.307-331.

[5]. Mofijur, M., Mahlia, T.M.I., Silitonga, A.S., Ong, H.C., Silakhori, M., Hasan, M.H., Putra, N. and Rahman, S.A., 2019. Phase change materials (PCM) for solar energy usages and storage: An overview. Energies, 12(16), p.3167.

[6]. Elias, C.N. and Stathopoulos, V.N., 2019. A comprehensive review of recent advances in materials aspects of phase change materials in thermal energy storage. Energy Procedia, 161, pp.385-394.

[7]. Kapoor, R., Ghosh, P., Tyagi, B., Vijay, V.K., Vijay, V., Thakur, I.S., Kamyab, H., Nguyen, D.D. and Kumar, A., 2020. Advances in biogas valorization and utilization systems: A comprehensive review. Journal of Cleaner Production, 273, p.123052.

[8]. Rathore, P.K.S. and Shukla, S.K., 2019. Potential of macroencapsulated PCM for thermal energy storage in buildings: A comprehensive review. Construction and Building Materials, 225, pp.723-744.

[9]. Suwaileh, W., Pathak, N., Shon, H. and Hilal, N., 2020. Forward osmosis membranes and processes: A comprehensive review of research trends and future outlook. Desalination, 485, p.114455.

[10]. Varga, B.O., Sagoian, A. and Mariasiu, F., 2019. Prediction of electric vehicle range: A comprehensive review of current issues and challenges. Energies, 12(5), p.946.

[11]. Seme, S., Štumberger, B., Hadžiselimović, M. and Sredenšek, K., 2020. Solar photovoltaic tracking systems for electricity generation: A review. Energies, 13(16), p.4224.

[12]. Ghosh, A., 2020. Potential of building integrated and attached/applied photovoltaic (BIPV/BAPV) for adaptive less energy-hungry building's skin: A comprehensive review. Journal of Cleaner Production, 276, p.123343.

[13]. Shekarchi, N. and Shahnia, F., 2019. A comprehensive review of solar-driven desalination technologies for off-grid greenhouses. International Journal of Energy Research, 43(4), pp.1357-1386.

[14]. Babu, T.S., Vasudevan, K.R., Ramachandaramurthy, V.K., Sani, S.B., Chemud, S. and Lajim, R.M., 2020. A comprehensive review of hybrid energy storage systems: Converter topologies, control strategies and future prospects. IEEE Access, 8, pp.148702-148721.

[15]. Sharma, A. and Chauhan, R., 2022. Integrated and separate collector storage type low-temperature solar water heating systems with latent heat storage: A review. Sustainable Energy Technologies and Assessments, 51, p.101935.